

new
runner

Blast Freezers – BASIC Version

The BASIC range of blast freezers are the ideal appliance for chefs, pastry and ice cream makers who need reliability and simplicity. They are fitted with a simplified electronic control panel, intuitive and user-friendly, which allows chilling cycles to be set extremely rapidly.

Chilling or freezing cycle can be selected by time or according to a probe inserted in the core of the product.

There is the possibility to select the following programs:

- **Soft chilling:** positive "delicate" temperature reduction (+3°C);
- **Hard chilling:** positive "rapid" temperature reduction (+3°C in 90'minutes), during this phase it reaches -20°C air temperature;
- **Freezing:** deep freezing or freezing (-18°C in 240'minutes) during this phase it reaches -40°C air temperature.

A wide range of products, from small countertop freezers with capacity for three GN 2/3 trays to the spacious freezers with capacity for fifteen GN 1/1 or 40x60 cm trays.



TECHNICAL DATA:

		BCB/10	BCB/10P
External dimensions (WxDxH)	cm	80x78x170	80x78x170
Trays capacity (trays pitch mm 67)	nr	10 GN 1/1 10 EN (60x40)	10 GN 1/1 10 EN (60x40)
Yield *		+90/+3°C = 34 Kg +90/-18°C = 22 Kg	+90/+3°C = 43 Kg +90/-18°C = 32 Kg
Max absorbed power **	W	2245	3475
Refrigerated power ***	W	1885	2710
Gas		R452A	R452A
Defrosting system		Automatic with pause	Automatic with pause
Working cycle: by time		yes	yes
Working cycle: by probe		yes	yes
Input voltage		1x230V – 50Hz	3x400V – 50Hz
Climatic class		5	5

*With ambient temperature of +32°C – load of standard sample of 125 gr. according to DIN 8953/8954

Evap. -10°C cond. +45°C *ASHRAE (Evap. -23,3°C cond. +54,4°C) ***Evap. -10°C cond. +45°C ***ASHRAE (Evap. -23,3°C cond. +54,4°C)



Core probe




Detail of internal ventilation




Control board

INSTALLATION DIAGRAM:



Electricity supply: 3x1.5 mm² wire complete with Schuko plug; L=4000 mm

ACCESSORIES AND OVERPRICES ON REQUEST:



45100202 Pastry structure for no. 10 60x40 trays, pitch mm 16,5 for BCB/10 (overprice)



45020503 Pair of guides for 60x40 trays structure



45000540 Set of castors Ø 100 mm

45100235 Water cooled condensing unit for BCB/10 (overprice)

45100240 Stainless steel GN 1/1 rack

45100242 Stainless steel 60x40 cm rack

40200560 60Hz frequency (overprice)