

delice



Pastry refrigerated and freezer cabinets



The DELICE cabinets can accommodate trays measuring 60x40 or 60x80 cm and in the pastry version they are equipped with 20 pairs of runners for trays support. Made entirely in stainless steel, by respecting the highest possible quality standards, they feature 75 mm thick insulation produced by injecting HCFC-free polyurethane resins, with utmost respect for the environment.

They have a radial bottom to enable optimum hygiene and easy cleaning, and a slot-in easy replaceable magnetic seal. The temperature is controlled by an easy-to-read and programming electronic panel that enables the maximum precision of any working cycle.

Supplied with "energy save" function.



TECHNICAL DATA:

Insulation thickness	mm
External dimensions (WxDxH)	mm
Capacity	lt
Doors	nr
Trays capacity	nr
Equipment (pair of runners)	nr
Rack with trays pitch (74 positions)	mm
Electronic control	
Refrigeration type	
Temperature	°C
Defrosting type	
Condensate water elimination	
Max absorbed power *	W
Refrigeration power	W
Gas	
Input voltage	
Climatic class	

	ARP/20	ARP/20B
Insulation thickness	75	75
External dimensions (WxDxH)	790x690x2140	790x690x2140
Capacity	500	500
Doors	1	1
Trays capacity	20 600x400	20 600x400
Equipment (pair of runners)	20	20
Rack with trays pitch (74 positions)	16,5	16,5
Electronic control	touch control	touch control
Refrigeration type	indirect/soft ventilated	indirect/soft ventilated
Temperature	-2/+8	-22/-10
Defrosting type	automatic by hot gas	automatic by hot gas
Condensate water elimination	automatic	automatic
Max absorbed power *	500	795
Refrigeration power	605*	650**
Gas	R290	R290
Input voltage	1x230V/50Hz	1x230V/50Hz
Climatic class	5	5

*Evap. -10°C cond. +45°C / **ASHRAE (Evap. -23,3°C cond. +54,4°C)



S/s rack for runners, 74 positions



Touch control board

ACCESSORIES AND SURCHARGES ON REQUEST:



Pair of runners for cm 60x40 tray



Rilsan cm 60x40 shelf

S/s cm 60x40 shelf



S/s cm 40x60x2h tray

S/s cm 40x60x3h tray



Toughened glass door with internal LED light (surcharge)



Set of Ø 100 castors



Prearranged version with valve system (deduction)



Wi-Fi supervising system (surcharge)



60Hz frequency

INSTALLATION DIAGRAM:

